



## D-BELAY STATION 316L DRACO

**Ref: V41410**

Belay Station Type D in 316L stainless steel for outdoor environment / eco tri zinc plated for indoor environment. Two fixing points consisting of hanger Fixe1 at the top end and Fixe 1 at lower end, both of them for M10 / M12 screws. Anchor point with Draco. COMPONENT FEATURES Hanger Fixe 1 - Geometry: Rounded inner edge for less wear on the carabiners. Directs the carabiner for an optimal roof work. Conical Washer. Better control of the tightening torque. Three anti-rotation pins. Optimized surface for full contact. Fixe 1 - Hanger features: For bolts M10 / M12. Weight: 57g (10mm) / 56g (12mm). Breaking strength: 25 kN. Material: ecotri zinc plated / 316L stainless steel. Ring features: Ring always present between components for a better workability. TIG welding. Better resistance to corrosion. Inside diameter: 33mm. Breaking strength: 25 kN. Material: ecotri zinc plated / 316L stainless steel. Features of the 316L stainless steel-chain: TIG welding. Better resistance to corrosion. Reduction of the number of links to three. Less critical points. 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25 kN. Material: 316L stainless steel. Features of the ecotri zinc plated-chain: 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: ecotri zinc plated steel. Draco carabiner features: Keylock closing Oversized friction zone. Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Are you sure this is your ideal belay station Find it out: <https://www.fixeclimbing.com/configurator/>

### Información técnica:

|                    |       |
|--------------------|-------|
| Brand:             | Fixe  |
| Diameter:          | 10mm  |
| Country of origin: | Spain |
| Color:             | Inox  |
| Material:          | 316L  |
| Breaking Strength: | 25kN  |
| Configurator:      | Si    |