



AUTO BELAY PERFECT DESCENT DIRECT DRIVE

Ref: PDD-28-DC

The Direct Drive™ Auto Belay from Perfect Descent Climbing Systems

The Direct Drive™ Auto Belay from Perfect Descent Climbing Systems features a sealed casing, industry leading price, and is EN compliant. This model is the ideal auto belay solution for applications where speed is not a factor. The Direct Drive™ is perfect for beginner routes, kid zones, and programmed events. Outfit your operation for less!

Budget-friendly:

- Perfect Descent is the cost leader in auto belays and boasts the lowest average cost of ownership over the life of the unit.
- The lightweight and compact design equate to lower shipping costs when returning units for factory authorized service and recertification.
- A growing network of factory authorized service centers makes it quick and simple to keep your units in service and on the wall.

Craftsmanship, safety, and innovation:

- Perfect Descent Auto Belays are hand built in Colorado, USA, feature a high-grade stainless steel and aluminum housing (no plastic), and are never mass produced.
- Internal components are made of high-quality materials that stand up to repeated use and require little-to-no maintenance.
- All devices go through rigorous quality assurance before shipping and meet global safety standards.

Versatile and durable device housing:

- Perfect Descents are the lightest and most compact modular auto belay on the market, a key feature for easy hauling and mounting.
- The new multi-point installation handle provides flexible mounting options and independent backup eyes.
- All units are sealed for outstanding performance both indoors and outdoors.

Lanyards to love:

- Easy to replace lanyards take minutes to change and can be performed in the field by the end user.
- Choose from the lanyard length that best meets your needs: 28 ft, 40 ft, or 53 ft (8.5 m, 12.2 m, or 16.1 m).
- High quality nylon webbing is more user-friendly than cable-based systems and won't damage walls.
- The built-in wear indicator takes the guesswork out of knowing when it's time to replace your lanyard.
- An anodized aluminum nozzle is integrated with the lanyard for durability and performance.
- Choose from two 3-stage, swivel carabiner options: aluminum for corrosive environments or to reduce weight and steel alloy for durability. Or choose the Dual Connection option with swivel, nylon Y dogbone tether, and dual aluminum, 3-stage captive pin carabiners.



NOTE: The user may replace long lanyards with shorter lanyards to accommodate lower mounting heights. Never replace a shorter lanyard with a longer lanyard as the unit will not operate properly. Longer lanyards can only be installed by C3 Manufacturing or an authorized service center.

IMPORTANT: Perfect Descent Auto Belays are designed to be controlled lowering devices used in vertical climbing activities and are not suitable for use in jumping-type activities that create shock loading forces. Repeated shock loading of the device can damage the internal components, and in some cases, may result in failure of the unit. The lanyard should always be equivalent to or greater in length than the anticipated mounting height. Units with excessive lanyard length may experience improper lanyard spooling that can result in jerky or rapid descent. Always select the lanyard that most closely matches the mounting height and avoid using long lanyards on short walls.

Specifications

- Weight: 29 - 31 lbs (13.1 - 14.1 kg)
- Housing Dimensions: 16 x 9.5 x 7.5 in (40 x 24 x 19 cm)
- Lanyard Retraction Speed: 2 ft/s (0.6 m/s)
- Maximum Descent Rate: 6.6 ft/s (2 m/s)
- Minimum Descent Rate: 1.6 ft/s (0.5 m/s)
- Housing Material(s): Stainless Steel, Aluminum, and Acetal
- Nozzle Material(s): Anodized Aluminum
- Lanyard Material(s): 1 in (2.5 cm) Wide Nylon Webbing
- Lanyard Breaking Strength: 3,500 lbs (15.6 kN)
- Lanyard Length(s): 28, 40, or 53 ft (8.5, 12.2, or 16.1 m)
- User Weight Range: 25 - 310 lbs (11.5 - 140 kg)

Certifications

- ANSI/ASSE Z359.4: Safety Requirements for Assisted-Rescue and Self Rescue Systems, Subsystems, and Components
- Conforms with EN341: 2011-1A/RFU PPE-R/11.128 Version 1 and EN360: 2002. - Requires periodic recertification every 12 months or sooner as determined by a Competent Person
- AS/NZS 1891: Industrial Fall-Arrest Systems and Devices - Part 3: Fall Arrest Devices
- CSA Z259.2.3-99: Descent Control Devices

Información técnica:

Brand:	PERFECT DESCENT
Country of origin:	USA
Material:	Double Aluminium Carabiner
Configurator:	No
Size long:	8.5 m