

C-BELAY STATION ECOTRI CHAIN

Ref: V03212

Individual Belay Station Type C in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Fixing point consisting of hanger Fixe1 for M10 / M12 screws. Anchor point with ring. Designed and manufactured in Barcelona-Pirineus. COMPONENT FEATURES Hanger Fixe 1 - Geometry: Rounded inner edge for less wear on the carabiners. Directs the carabiner for an optimal roof work. Conical Washer. Better control of the tightening torque. Three anti-rotation pins. Optimized surface for full contact. Fixe 1 - Hanger features: For bolts M10 / M12. Weight: 57g (10mm) / 56g (12mm). Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Ring features: Ring always present between components for a better workability. TIG welding. Better resistance to corrosion. Inside diameter 33mm. Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Features of the 316L stainless steel-chain: TIG welding. Better resistance to corrosion. Reduction of the number of links to three. Less critical points. 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: 316L stainless steel. Features of the ecotri zinc plated-chain: 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: ecotri zinc plated steel. Are you sure this is your ideal belay station Find it out: https://www.fixeclimbing.com/configurator/

Información técnica:

| Brand: | Fixe |
|--------------------|--------|
| Country of origin: | Spain |
| Color: | Ecotri |
| Material: | Steel |
| Breaking Strenght: | 25kN |
| Configurator: | Si |
| Diameter: | 12mm |
| | |