



V-BELAY STATION ECOTRI

Ref: V50212

Type V meeting in 316L stainless steel for outdoor environments / ecotri zinc-plated for indoor environments. Two fixing points composed of two Fixe 1 plates for M10 / M12 screws. Anchorage point with ring. Designed and manufactured in Barcelona-Pirineus. CHARACTERISTICS OF THE COMPONENTS

Fixe 1 plate geometry:

- Rounded inner edge for less carabiner wear.
- Directs the carabiner for optimum work on roofs.
- Conical Washer. More torque control.
- Three anti-rotation pins.
- Optimised surface for full contact.

Fixe 1 plate features:

- For M10/M12 screws.
- Weight: 57g (M10)/56 (M12).
- Ultimate strength: 25kN.
- Material: ecotri zinc plated steel / 316L stainless steel.

Features of the ring:

- Always present ring between components for better manoeuvrability.
- TIG welding. Better corrosion resistance.
- Inner diameter: 33mm.
- Limit resistance: 25kN.
- Material: ecotri zinc plated steel / 316L stainless steel.

Characteristics of 316L stainless steel chain:

- TIG welding. Better corrosion resistance.
- Reduction of the number of links to three. Fewer critical points.
- Link rod diameter: 7mm.
- Useful length: 185mm.
- Ultimate strength: 25kN.
- Material: 316L stainless steel.

Features of ecotri zinc plated steel chain:

- Link rod diameter: 7mm.
- Working length: 185mm.
- Ultimate strength: 25kN.
- Material: ecotri zinc plated steel.

Belay Station Type V in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Two fixing points consisting of two Fixe 1 hangers M10 / M12 screws. Anchor point with ring. Designed and manufactured in Barcelona-Pyrenees.

COMPONENT FEATURES

Hanger Fixe 1 - Geometry: Rounded inner edge for less wear on the carabiners. Directs the carabiner for an optimal roof work. Conical Washer. Better control of the tightening torque. Three anti-rotation pins. Optimized surface for full contact.

Fixe 1-Hanger features: For bolts M10 / M12. Weight: 57g (10mm) / 56g (12mm). Breaking strength: 25 kN. Material: ecotri zinc plated / 316L stainless steel.

Ring features: Ring always present between components for a better workability. TIG welding. Better resistance to corrosion. Inside diameter 33mm. Breaking strength: 25 kN. Material: ecotri zinc plated / 316L stainless steel.

Features of the 316L stainless steel-chain: TIG welding. Better resistance to corrosion. Reduction of the number of links to three. Less critical points. 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: 316L stainless steel.

Features of the ecotri zinc plated-chain: 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: ecotri zinc plated steel.

Información técnica:

Brand:	Fixe
Country of origin:	Spain
Color:	Ecotri
Material:	Steel
Breaking Strenght:	25kN
Configurator:	Si
Diameter:	12mm