



8,8 PEDRAFORCA

Ref: C422880060

The Pedraforca

This all-purpose rope has triple standardisation (simple, double and twin) and is the one most frequently chosen by mountain guides. Climbers use it for alpine ascents, climbing a big wall or working on a tough sport climbing project. Its Fusion construction provides extra security on winding paths to overcome sharp rocks and ridges. Less than 9 mm in diameter, this rope performs marvellously on all types of terrain with a unique touch and durability.

Technology

- Diameter: 8.8 mm.
- Standardisation: triple standardisation. Simple, double and twin.
- Full Dry treatment: Water-repellent treatment on the sheath and core. Totally waterproofs the rope. Provides resistance to oil, grease, and water. Extends the rope's lifespan. UIAA water repellent standard.
- Endurance construction: It favors sliding and extends the rope s lifespan. Braided with 36 threads.
- Fusion: Prevents sheath slippage. The rope's performance is extended by the firm union of the sheath and the core.

Finishes:

- Middle Mark: indicates the halfway point on the rope with a black mark.
- 8 Mark: marking system that uses a red mark to indicate that there are 8 meters left to reach the end of the rope.
- Reflector: reflective indicator at both ends of the rope
- Ultrasonic cut: stiffens the rope ends and protects them from wear.

Lengths available: 40, 50, 60, 70, 80, 100, and 200 meters. Colours available: Purple and Yellow.
Manufactured in: Sant Quirze de Besora (Barcelona – Pyrenees).

Technical information

N Falls 6/6/14 - Weight 54g/m - Impact force 7.2/7.2/7.4KN - Slippage 0mm - Dynamic Elong. 37/37/24% - Static Elong. 7/7/5% - Sheath 30%

Packaging info

Vegetal Base INK 27% Recycled material 100% Recyclable material 4% Synthetic (40% recycled)

Información técnica:

Brand: Fixe

Country of origin: Barcelona - Pyrenees (Spain)

Color: Violet



Material: Polyamide

Format: Bag Middle Mark: Yes

Treatment: Full Dry

Static Elongation: 7% single / 7% half / 5% twin

Number of Falls: 6 single/6 half/14 twin

Impact Force: 7,2 single / 7,2kN half / 7,4kN

twin

Sheat Slipage: 0,0mm

Type of Sheat: Endurance

Single / Half / Twin Type of Rope:

37% single / 37% half / 24% twin Dinamic Elongation:

Configurator: No

Fusion: Yes

8m mark: Yes

Reflector: Yes

Ultrasonic finish: Yes

Size long: 60m

Diameter: 8,8mm