





## Ref: 300083

Model 220/230 Perfect Descent Replacement Lanyards are made from high quality, 1-inch nylon webbing. The eyecatching yellow and black color scheme and built-in wear indicator make it easy to see when your lanyards are due for replacement. Features: " Easy to replace lanyards take minutes to change and can be performed in the field by the end user. " Choose the lanyard length that best meets your needs: 28 ft, 40 ft, or 53 ft (8.5 m, 12.2 m, or 16.1 m). " High quality nylon webbing is more user-friendly than cablebased systems and won t damage walls. "The built-in wear indicator takes the guesswork out of knowing when it s time to replace your lanyard. " An anodized aluminum nozzle is integrated with the lanyard for durability and performance." Choose from 4 connection options: "3-stage aluminum swivel carabiner for corrosive environments or where weight reduction is needed, " 3-stage steel alloy swivel carabiner for durability, "Dual, 3-stage captive pin aluminum carabiners with nylon Y dogbone and integrated swivel, " Sewn loop for operator-supplied hardware including Self Belay and Belay Mate connectors. Chosen hardware should incorporate a swivel and must conform to the requirements of EN 362 and/or EN 12275 safety regulations. NOTE: The user may replace long lanyards with shorter lanyards to accommodate lower mounting heights. Never replace a shorter lanyard with a longer lanyard as the unit will not operate properly. Longer lanyards can only be installed by C3 Manufacturing or an authorized service center.

Información técnica:

Marca: PERFECT DESCENT

Country of origin: USA

Material: Aluminium Carabiner

Configurator: No

Size long: 16m